



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION



CERTIFICATE No.: 2019200907000112

NAME AND ADDRESS OF THE APPLICANT

Mibbo (Xia men) Automation Technology Co., Ltd
E802A,Taiwan Technology Business Incubator,Torch (Xiang' an) Industrial
Park,Xiamen,Fujian

NAME AND ADDRESS OF THE MANUFACTURER

Mibbo (Xia men) Automation Technology Co., Ltd
E802A,Taiwan Technology Business Incubator,Torch (Xiang' an) Industrial
Park,Xiamen,Fujian

NAME AND ADDRESS OF THE FACTORY

Mibbo (Xia men) Automation Technology Co., Ltd
6th Floor, 313-315 Xiangtian Road, Xiang 'an District, Xiamen City, Fujian Province,
China

NAME, MODULE AND SPECIFICATION

Switching Power Supply
见证书附件

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T9254.1-2021 (Class A); GB 4943.1-2022; GB 17625.1-2022 (Class A)

This is to certify that the above mentioned products have met the requirements of
implementation rules for compulsory certification(REF NO. CNCA-C09-01: 2023)

Data of issue: 2023.10.11


Data of expiry: 2024.07.10

Validity of this certificate is subject to positive result of the regular follow up inspection by
issuing certification body until the expiry date.

Date of original certification: 2019.07.11

The certificate can be verified through CNCA's website :www.cnca.gov.cn or CEPREI's TEL:+86-20-87236606

Accredited by China National Accreditation Service for Conformity Assessment CNAS C012-P



CEPREI

General Manager:

CEPREI CERTIFICATION BODY

No. 76 West of Zhucun Avenue, Zhucun, Zengcheng District, Guangzhou, China
<http://www.ceprei.org>





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

Appendix:

Page 1 of 1

Registration Number: 2019200907000112

Model : MTS150-XF/XFL/XFP/XFPL X=3, 3, 4, 2, 05, 7, 5, 09, 12, 13, 8, 15, 19, 24, 27, 29, 36, 42, 48 denotes output voltage, “ F” represents the input voltage of 100-240VAC. “L” represents the switching power supply electrolytic capacitor can work at-40℃ at low temperature “P” represents the switching power supply pin terminal block “PL” represents the low temperature pin socket of switching power supply, not affect product safety and EMC)

Input: 100-240VAC, 50/60Hz, 3A

output:

No	Model	The output voltage	Output current	Output power
1	MTS150-3.3F, MTS150-3.3FL MTS150-3.3FP, MTS150-3.3FPL	3.3VDC	17A	56.1W
2	MTS150-4.2F, MTS150-4.2FL MTS150-4.2FP, MTS150-4.2FPL	4.2VDC	17A	71.4W
3	MTS150-05F, MTS150-05FL MTS150-05FP, MTS150-05FPL	5VDC	17A	85W
4	MTS150-7.5F, MTS150-7.5FL MTS150-7.5FP, MTS150-7.5FPL	7.5VDC	14.5A	108.75W
5	MTS150-09F, MTS150-09FL MTS150-09FP, MTS150-09FPL	9VDC	13.5A	121.5W
6	MTS150-12F, MTS150-12FL MTS150-12FP, MTS150-12FPL	12VDC	12.5A	150W
7	MTS150-13.8F, MTS150-13.8FL MTS150-13.8FP, MTS150-13.8FPL	13.8VDC	10.5A	144.9W
8	MTS150-15F, MTS150-15FL MTS150-15FP, MTS150-15FPL	15VDC	10A	150W
9	MTS150-19F, MTS150-19FL MTS150-19FP, MTS150-19FPL	19VDC	7.9A	150W
10	MTS150-24F, MTS150-24FL MTS150-24FP, MTS150-24FPL	24VDC	6.5A	156W
11	MTS150-27F, MTS150-27FL MTS150-27FP, MTS150-27FPL	27VDC	5.6A	151.2W
12	MTS150-29F, MTS150-29FL MTS150-29FP, MTS150-29FPL	29VDC	5.2A	150.8W
13	MTS150-36F, MTS150-36FL MTS150-36FP, MTS150-36FPL	36VDC	4.3A	154.8W
14	MTS150-42F, MTS150-42FL MTS150-42FP, MTS150-42FPL	42VDC	3.6 A	151.2W
15	MTS150-48F, MTS150-48FL MTS150-48FP, MTS150-48FPL	48VDC	3.3A	158.4W

Note: This appendix is effective when used in conjunction with the certificate.



CEPREI

General Manager:

CEPREI CERTIFICATION BODY

No. 76 West of Zhucun Avenue, Zhucun, Zengcheng District, Guangzhou, China
<http://www.ceprei.org>

